

Synthoil Race Tech GT1 10W-60

Description

Synthoil Race Tech GT1 SAE 10W-60 is a modern, fully synthetic, high-performance engine oil formulated for use in four-stroke engines under extreme load. The combination of synthetic base oils and modern additive technology satisfies the requirements of the latest engine designs.

Properties

- outstanding engine cleanliness
- mixable with all commercially available motor oils
- high lubrication reliability
- tested for catalytic converters
- optimum stability to aging
- optimum lubrication in extreme operating conditions
- rapid oil delivery at low temperatures
- extremely low oil consumption
- extremely low evaporation loss

Specifications and approvals:

ACEA A3 • ACEA B4 • API CF • API SL

Technical data

Viscosity at 40 °C	155 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	23,8 mm ² /s ASTM D 7042-04
Viscosity at -25 °C	<7000 mPas DIN 51377
Viscosity index	185 DIN ISO 2909
Color number (ASTM)	3,5 DIN ISO 2049
Density at 15 °C	0,855 g/cm ³ DIN 51757
Flash point	240 °C DIN ISO 2592
Pour point	-30 °C DIN ISO 3016
Evaporation loss (Noack)	6,5 % ASTM D 5800-08 Method B
Total base number	8,0 mg KOH/g DIN ISO 3771
Sulfate ash	1,2 g/100g DIN 51575
SAE class (engine oils)	10W-60 SAE J300



Areas of application

For petrol and diesel engines with and without turbocharging. Especially suitable for extreme engine requirements and racing.

Application

The operating instructions of the vehicle and engine manufacturers must be followed.

Available pack sizes

1 l Canister plastic	1390 D-GB-I-E-P
1 l Canister plastic	1943 D-RUS-UA
1 l Canister plastic	8908 D-NL-F-GR-ARAB
4 l Canister plastic	7535 D-RUS-UA
5 l Canister plastic	1391 D-GB-I-E-P
5 l Canister plastic	1944 D-RUS-UA
5 l Canister plastic	2876 D-DK-FIN-N-S
5 l Canister plastic	8909 D-NL-F-GR-ARAB
20 l Canister plastic	1392 D-GB-I-E-P
60 l Drum sheet metal	1393
205 l Drum sheet metal	1394
1000 l Container	1772
1 l Bulk goods	1399

Our information is based on thorough research and may be considered reliable, although not legally binding.