

Accessories - Regrooving

R Fix = round blade, W Fix = angle blade.

Ref. No.	Designation	Cutting width [mm]	Cutting depth [mm]	Weight [g]	Content	Qty
564 2803	R Fix 1	3 - 4	max. 7		20	1
564 2810	R Fix 2	5 - 6	max. 8		20	1
564 2827	R Fix 3	6 - 8	max. 10		20	1
564 2834	R Fix 4	9 - 10	max. 14		20	1
564 2841	R Fix 5	10 - 14	max. 16		20	1
564 2858	W Fix 1	3 - 4	max. 7		20	1
564 2865	W Fix 2	5 - 6	max. 8		20	1
564 2872	W Fix 3	6 - 8	max. 10		20	1
564 2889	W Fix 4	9 - 10	max. 14		20	1
564 2896	W Fix 5	10 - 14	max. 16		20	1
564 2906	W Fix 6	22 - 28	max. 16		10	1
564 1020	Gauge, for setting the cutting depth					1
519 1653	Tread depth gauge Measuring range [mm] 0 - 30					1
519 1828	Digital tread depth gauge Measuring range [mm] 0 - 35			112		1



564 2834



564 2889



564 1020



519 1653




519 1828



RUBBER CUT STATION

Tool stand and gauge for easy regrooving of truck tyres (17.5" - 24.5").

- Tyres can be regrooved on or off their rims
- Efficient working and loading/unloading of the tyres
- Low space requirement, secure holding of tyres
- Integrated setting gauge
- One roller is equipped with a brake preventing accidental tyre rotation
- Equipped with 2 castors, can be moved around in the workshop
- Rubber Cut tool not included in the delivery

Ref. No.	Designation	
518 3719	RUBBER CUT STATION ECO Specifications: Weight [kg] approx. 40 Size [L x W x H mm] 1100 x 1100 x 1150 Tyre width [mm] max. 500	•



518 3719